







+1 (920) 234 5113 
 +852 2635 2285 
 +44 (0) 7506 414504 
 +52 1 (442) 343 3172 
 email: info@gseint.com
 web: www.gseint.com



Oil-less Tankset

GSE500

Volume **1.06 cfm (30 L)**
 Pressure Range **72.6-116 psi (5-8 bar)**
 Fill Time **230 sec.**

- Permanently lubricated bearings
- Oil-less, non-lubricated cup and cylinder
- Long-life cup design
- Thin wall cylinder for good heat transfer
- Stainless-steel valves
- Pressure switch
- Pressure relief valve
- Pressure gauge

Specification

Model Number	GSE500A-20	GSE500A-30
Volume	0.71 cfm (20 L)	1.06 cfm (30 L)
Pressure Range	72.6-116 psi (5-8 bar)	72.6-116 psi (5-8 bar)
Fill Time	160 Sec.	230 sec.
<i>Rated Power</i>	560W	560W
Motor Type	PSC	PSC
Voltage/Frequency	220V/50Hz	220V/50Hz
Net Weight	33 lbs (15Kg)	55 lbs (25kg)

The information presented in this material is based on technical data and test results of nominal units. Its is believed to be accurate and reliable and is offered as an aid to help in the selection of GSE products. It is the responsibility of the user to determine the suitability of the product for their intended use and the user assumes all risk and liability whatsoever in connection therewith. GSE does not warrant, guarantee or assume any obligation or liability in connection with this information.

Technical Drawings

