







+1 (920) 234 5113 
 +852 2635 2285 
 +44 (0) 7506 414504 
 +52 1 (442) 343 3172 
 email: info@gseint.com
 web: www.gseint.com

Twin Headed Rocking Piston

ZW190



Max. Flow **2.01cfm (57lpm)**
 Max. Pressure **26.9psi (1.85bar)**
 Max. Vacuum **23.6"Hg (799mbar)**


- Permanently lubricated bearings
- Oil-less, non-lubricated cup and cylinder
- Long-life cup design
- Thin wall cylinder for good heat transfer
- Stainless-steel valves
- Capacitor as standard
- Field service ability
- Recoverable thermally protected motor

Other voltages and configurations available upon request

Specification

Model Number	ZW190A-39/1.85	ZW190B2-39/1.85
Open Flow	1.94cfm (55lpm)	2.01cfm (57lpm)
Max. Continuous Pressure	26.9psi (1.85bar)	26.9psi (1.85bar)
Max. Continuous Vacuum	23.6"Hg (799mbar)	23.6"Hg (799mbar)
Current At Rated Load	1.2A@1.4bar	2.4A@1.4bar
Power At Rated Load	240w@1.4 bar	240w@1.4 bar
Motor Type	PSC	PSC
Voltage/Frequency	220V/50Hz	110V/60Hz
Starting Current	3.6A	7.5A
Net Weight	8.4lbs(3.8kg)	8.4lbs(3.8kg)

Performance Chart



The information presented in this material is based on technical data and test results of nominal units. Its is believed to be accurate and reliable and is offered as an aid to help in the selection of GSE products. It is the responsibility of the user to determine the suitability of the product for their intended use and the user assumes all risk and liability whatsoever in connection therewith. GSE does not warrant, guarantee or assume any obligation or liability in connection with this information.

Technical Drawings

