

Twin-Headed Rocking Piston

ZW300

Max. Flow **3.28 cfm (93 lpm)**

Max. Pressure **33.4 psi (2.3 bar)**

Max. Vacuum **25.4"Hg (860 mmHg)**




- Permanently lubricated bearings
- Oil-less, non-lubricated cup and cylinder
- Long-life cup design
- Thin wall cylinder for good heat transfer
- Stainless-steel valves
- Capacitor as standard
- Field service ability
- Recoverable thermally protected motor
- Other voltage and configurations available upon request

Specification

Model Number	ZW300A-53/2	ZW300A-75/1.4
Open Flow	2.79 cfm (79 lpm)	2.79 cfm (79 lpm)
Max. Continuous Pressure	33.4 psi (2.3 bar)	29 psi (2 bar)
Max. Continuous Vacuum	25.1"Hg (850 mmHg)	25.4"Hg (860 mmHg)
Current At Rated Load	1.5A	1.7A
Power At Rated Load	320W	370W
Motor Type	PSC	PSC
Voltage/Frequency	220V/50Hz	220V/50Hz
Starting Current	4.5A	5A
Net Weight	12.1 lbs (5.5kg)	12.8 lbs (5.8kg)

Performance Chart



The information presented in this material is based on technical data and test results of nominal units. Its is believed to be accurate and reliable and is offered as an aid to help in the selection of GSE products. It is the responsibility of the user to determine the suitability of the product for their intended use and the user assumes all risk and liability whatsoever in connection therewith. GSE does not warrant, guarantee or assume any obligation or liability in connection with this information.

Technical Drawings

